

TRANSFORMADORES DE MEDIDA (ENCAPSULADOS EN RESINA)



PRIMARIO BOBINADO								
MODELO	TU3aR		TU3bR		TU3R		TU50R	
Precisión	0,5	1	0,5	1	0,5	1	0,5	1
I _{pn} (A)	VA		VA		VA		VA	
5	2,5	5	10	20				
10	2,5	5	10	20				
15	2,5	5	10	20				
20	2,5	5	10	20				
25	2,5	5	10	20				
30	2,5	5	10	20				
40	2,5	5	10	20				
50	2,5	5	10	20	15	25		
60	2,5	5	10	20	15	25		
75	2,5	5	10	20	15	25		
100	2,5	5	10	20	15	25		
125	2,5	5	10	20	15	25		
150	2,5	5	10	20	15	25		
200	2,5	5	10	20	15	25		
250	2,5	5			15	25		
300	2,5	5			15	25		
400					15	25	15	25
500					15	25	15	25
600					15	25	15	25
750							15	25
800							15	25

DIMENSIONES

TU3aR

70 (height), 74 (total height), 33 (width), 36 (depth), 65 (width)

TU3R - TU3bR - TU50R

Soporte de fijación

110, 6,5, 21,5, 80, 36, 60, 90, 95, C, H, M.12, A, B, D, E, F, G, I

(*) M.8 de 5/5 A a 125/5 A
 (*) Diámetro 8,5 de 150/5 A a 300/5 A

MODELOS	Relación	A	B	C	D	E	F	G	H	I
TU3R	50/5-300/5	80	73,5	96	30	5	110	38	42	140
TU3R	400/5-600/5	80	73,5	101	30	10	110	48	47	140
TU50R	400/5-800/5	100	73,5	100	50	10	135	48	50	175
TU3bR	5/5-200/5	77	55	90	25	5	100	32	47	126

Dimensiones en mm.